



EN ISO 20345:2011



ENDURANCE  
**ROTOR BOA®**  
81375-00L

**S3 CI SRC**

**Size:** 36-48  
**Weight:** 800 gr.

**Fit:** 11

**Working Environment:**  
Building, Wood-metal carpentry,  
Mountains, Cold places



## FEATURES

### UPPER

Grain leather Hydro 1,8-2,0 mm  
Reflex insert  
Full Grain leather Hydro

### LINING

3D Air circulation 320 gr.  
GenuineWool Polar

### ANTISLIP LINING

DUALMICRO

### INSOLE

Dual insulation

### TOE CAP

Fiber cap SXT

### RESISTANCE TO PERFORATION

KX Antiperforation PS

### TYPE

Ankle boot

### SOLE

#### PU DUAL-DENSITY SRC

Two-component PU sole with anti-wear scaff cap and high-comfort in-between insole. Outsole with self-cleaning tread pattern, with a formula designed to ensure greater grip. SRC Antislip standard.

## TECHNOLOGIES


### Removable Insole



Insole perfect for winter use and for footwear with protection against cold "CI". It consists of a highly resistant and absorbing felt piece that keeps the foot dry and warm and of an aluminised film to isolate the foot from the ground.



### Protection elements



Composite toe cap with fiberglass. Resistant to over 200J. Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



### Lateral stability

**dynamicHC control**  
technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



### Torsional stability

**STABIL•ACTIVE**

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



### Electrical features



Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



### Other



**FIT TO GO FURTHER™**

A patented closing system with a multi coated stainless steel cable. The BOA® Fit System delivers micro-adjustable precision fit, engineered to perform in the toughest conditions.



## SRC (SRA+SRB)



SOLE 81  
PU - PU

Category	Flat (mm)	Heel (mm)	Value
SRA CERAMIC + DETERGENT SOLUTION	≥0.32	≥0.28	0.52
SRB STEEL + GLYCEROL	≥0.18	≥0.13	0.23

EN ISO 20344:2011